

# 200401

For more information about this assembly solution,

please contact us at the e-mail address below:

[fastenerlisi@lisi-group.com](mailto:fastenerlisi@lisi-group.com)



**Categories:** Our Products, Serrated washers, Serrated washers with internal teeth (JZ), Washers

## Product Short Description :

---

Our « Serrated washers » family has been designed to ensure secure fastening over time for all assembly challenges. It is usually used before a locknut, and acts as an anti-vibration device. It also prevents an inadvertently loosening.

This family includes a complete range of products: with internal and external teeth, for different screw diameters, etc.

---

## Additional Information:

- Dimensions: N/A
- Weight: N/A
- External diameter tolerance: + / -0.29
- Ø External [d2] (mm): 8.00
- Ø Internal [d1] (mm): 4.10

- Internal diameter tolerance: +0,30
- Material: C60S to C75S
- Maximum hardness [HV]: 480
- Minimum hardness [HV]: 400
- Screw diameter: M 4
- Screw diameter (US): 5/32
- Number of teeth (min): 8
- Thickness [e] (mm): 0.50
- Thickness tolerance:  $\pm 0,03$
- Heat treatment: Yes

For more information about this assembly solution,

please contact us at the e-mail address below:

[fastenerlisi@lisi-group.com](mailto:fastenerlisi@lisi-group.com)

