

550617

For more information about this assembly solution,

please contact us at the e-mail address below:

fastenerlisi@lisi-group.com



Categories: Contact washers, Our Products, Tooth contact washers, Washers

Product Short Description :

Our “Contact washers” family has been designed to ensure secure fastening over time for all assembly challenges. They prevent loosening of threaded assemblies due to vibration or temperature variations.

This family includes a complete range of products: some of them can be used separately, others have been designed to be assembled on a nut or a screw, they can ensure electrical continuity, etc.

Additional Information:

- Dimensions: 2.25 cm
- Weight: N/A
- External diameter tolerance: + / -0.35
- Ø External [d2] (mm): 18.00

- Height tolerance: +0, 030, 30
- Height (mm): 2.25, 2.55
- Ø Internal [d1] (mm): 6.10
- Internal diameter tolerance: +0, 036, 36
- Material: C60S to C67S
- Maximum hardness [HV]: 510
- Minimum hardness [HV]: 420
- Number of ridges (min): 45, 6
- Screw diameter: M 6
- Minimum teeth height (mm): 0.3
- Number of teeth (min): 6
- Thickness [e] (mm): 1.40
- Thickness tolerance: $\pm 0, 004, 04$
- Heat treatment: Yes

For more information about this assembly solution,

please contact us at the e-mail address below:

fastenerlisi@lisi-group.com

